




Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

GRIPPER® MECHANICAL PLUGS

- Ideal for plumbing system tests
- Easy to install with extra-large wing nut
- Inside of pipe seals inside pipe as far as needed
- Made with glass-reinforced ABS plastic
- End-of-pipe seals only at the end of a pipe, preventing plug from falling into stack

270 210	1-1/2"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 229	2"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 237	3"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 245	4"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 261	6"	End of Pipe Gripper® Plug	10	17 PSI	40FT
270 270	8"	End of Pipe Gripper® Plug	10	17 PSI	40FT
<hr/>					
270 296	4"	Inside of Pipe Gripper® Plug	10	17 PSI	40FT
270 253	6"	Inside of Pipe Gripper® Plug	10	17 PSI	40FT
270 288	8"	Inside of Pipe Gripper® Plug	10	17 PSI	40FT



HUB-FIT GRIPPER® PLUGS

- Ideal for use in hub fittings and in bell-end pipe
- Pressure rated for conducting DWV tests
- Yellow color enhances visibility in pipe
- Made with glass-reinforced ABS plastic and natural rubber O-ring

270 528	2"	Hub-Fit Gripper® Plug	10	13 PSI	30FT
270 538	3"	Hub-Fit Gripper® Plug	10	13 PSI	30FT
270 548	4"	Hub-Fit Gripper® Plug	10	13 PSI	30FT



CLEAN-OUT GRIPPER® PLUGS

- Patented threaded O-ring ensures airtight seal
- Stainless steel hardware prevents corrosion
- Black color blends well with cast-iron pipe
- NPT-sized, including hard-to-find 3-1/2"
- Guaranteed to seal all damaged threads
- Made with glass-reinforced ABS plastic and natural rubber O-ring

270 168	2"	Clean-Out Gripper® Plug	10	17 PSI	40FT
270 178	3"	Clean-Out Gripper® Plug	10	17 PSI	40FT
270 138	3-1/2"	Clean-Out Gripper® Plug	10	17 PSI	40FT
270 188	4"	Clean-Out Gripper® Plug	10	17 PSI	40FT



T-HANDLE ALUMINUM GRIPPER® PLUGS (UNDERGROUND)

- Can be used in long-term applications
- Chemical-resistant neoprene O-ring
- Made of heavy-duty aluminum
- Bypass can be used to conduct sewer air pressure test

272 949	6"	Gripper® Plug 1/4" Bypass	1	17 PSI	40FT
272 957	8"	Gripper® Plug 3/4" Bypass	1	17 PSI	40FT
272 965	10"	Gripper® Plug 3/4" Bypass	1	17 PSI	40FT
272 973	12"	Gripper® Plug 3/4" Bypass	1	13 PSI	30FT
272 981	15"	Gripper® Plug 3/4" Bypass*	1	13 PSI	30FT
272 998	18"	Gripper® Plug 3/4" Bypass*	1	8.7 PSI	20FT



*Concrete and clay pipe sizes only.

T-HANDLE ALUMINUM GRIPPER® PLUGS (UNDERGROUND)

- Can be used in long-term applications
- Chemical-resistant neoprene O-ring
- Made of heavy-duty aluminum

272 892	6"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 906	8"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 914	10"	Gripper® Plug (Non By-Pass)	1	17 PSI	40FT
272 922	12"	Gripper® Plug (Non By-Pass)	1	13 PSI	30FT
272 930	15"	Gripper® Plug (Non By-Pass)*	1	13 PSI	30FT
272 888	18"	Gripper® Plug (Non By-Pass)*	1	8.7 PSI	20FT



*Concrete and clay pipe sizes only.

REPLACEMENT O-RINGS (UNDERGROUND)

- Designed for T-handle aluminum gripper plugs
- Neoprene O-ring is chemical-resistant

017 895	6"	Replacement O-Ring	1		
006 105	8"	Replacement O-Ring	1		
006 113	10"	Replacement O-Ring	1		
014 746	12"	Replacement O-Ring	1		
006 145	15"	Replacement O-Ring*	1		
017 863	18"	Replacement O-Ring*	1		



*Concrete and clay pipe sizes only.

Category 12 Mechanical Test Plugs & Accessories


12



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

IRON GRIP™ MECHANICAL BY-PASS PLUGS

- Wing-nut design allows for easy installation with tools
- Can be used as a permanent or temporary plug
- Cast-iron bypass design can be used for water test or sewer air testing



268 028	2"	Iron Grip™ Plug	3/8" Bypass	1	13 PSI	30FT
268 038	3"	Iron Grip™ Plug	1/2" Bypass	1	11 PSI	25FT
268 048	4"	Iron Grip™ Plug	1/2" Bypass	1	8.7 PSI	20FT
268 068	6"	Iron Grip™ Plug	1/2" Bypass	1	4.3 PSI	10FT
268 088	8"	Iron Grip™ Plug	1/2" Bypass	1	4.3 PSI	10FT
268 108	10"	Iron Grip™ Plug	1/2" Bypass	1	3.5 PSI	8FT
268 128	12"	Iron Grip™ Plug	1" Bypass	1	2.6 PSI	6FT

ECON-O-GRIP® PLUGS

- Cost-effective method for plugging open-ended pipe
- Natural rubber O-ring
- Effective pipe dust cover
- Not recommended for pressure tests



271 519	1-1/2"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 527	2"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 535	3"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 543	4"	Econ-O-Grip® Plug		10	2 PSI	5FT
271 551	5"	Econ-O-Grip® Plug		5	1 PSI	2FT
271 578	6"	Econ-O-Grip® Plug		5	1 PSI	2FT

PETRO ECON-O-GRIP® PLUGS (CHEMICAL RESISTANT)

- Chemical-resistant Nitrile rubber and stainless steel hardware
- Not recommended for pressure tests



273 318	1-1/2"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 328	2"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 338	3"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 348	4"	Stainless Steel Econ-O-Grip® Plug		2	2 PSI	5FT
273 358	5"	Stainless Steel Econ-O-Grip® Plug		1	1 PSI	2FT
273 368	6"	Stainless Steel Econ-O-Grip® Plug		1	1 PSI	2FT

SURE-GRIP® PLUGS - NEW DESIGN!

- Polypropylene construction with natural rubber O-ring
- Can be used as a permanent or temporary plug
- Fits all type of pipe at nominal sizes



271 158	1-1/2"	Sure-Grip® Plug		10	22 PSI	50FT
271 208	2"	Sure-Grip® Plug		10	22 PSI	50FT
271 308	3"	Sure-Grip® Plug		10	13 PSI	30FT
271 408	4"	Sure-Grip® Plug		10	13 PSI	30FT

KWIK 'N SURE® PLUGS

- Works in all types of pipe
- Wing nut on 3/8" - 1-1/4" sizes
- Hex nut on 1.5" through 5" sizes
- Works well for plugging water line stub-outs
- Natural rubber O-ring



269 832	0.39"	Kwik 'n Sure Plug		1	185 PSI	428FT
269 840	1/2"	Kwik 'n Sure Plug		1	180 PSI	415FT
269 867	3/4"	Kwik 'n Sure Plug		1	180 PSI	415FT
269 875	1"	Kwik 'n Sure Plug		1	40 PSI	92FT
269 883	1-1/4"	Kwik 'n Sure Plug		1	112 PSI	2588FT
269 891	1-1/2"	Kwik 'n Sure Plug		1	88 PSI	203FT
269 905	2"	Kwik 'n Sure Plug		1	112 PSI	258FT
269 913	2-1/2"	Kwik 'n Sure Plug		1	72 PSI	166FT
269 921	3"	Kwik 'n Sure Plug		1	28 PSI	65FT
269 948	4"	Kwik 'n Sure Plug		1	24 PSI	558FT
269 956	5"	Kwik 'n Sure Plug		1	8 PSI	18FT

MONITOR WELL™ LOCKING PLUGS

- Designed to seal monitor wells
- Sized to seal schedule 40 piping
- 2" and 4" sizes can also seal schedule 5 plastic and stainless steel pipe
- Yellow chromate-coated locking latch accepts Cherne's solid brass padlock or No. 2 Master®, padlock
- Meets all EPA requirements for locking plugs
- Made with chemical-/petroleum-resistant Estaloc® plastic top/bottom plates and Nitrile sealing O-ring
- Comes with stainless steel carriage bolt



271 648	1"-1-1/4"	Monitor Well™ Locking Plug		12	6.5 PSI	15FT
271 675	2"	Monitor Well™ Locking Plug		50	6.5 PSI	15FT
271 669	3"	Monitor Well™ Locking Plug		75	6.5 PSI	15FT
271 683	4"	Monitor Well™ Locking Plug		25	6.5 PSI	15FT
271 691	6"	Monitor Well™ Locking Plug		8	6.5 PSI	15FT
271 735	8"	Monitor Well™ Locking Plug		1	6.5 PSI	15FT
112 941		Padlock with Key		1	6.5 PSI	15FT

Category 12 Mechanical Test Plugs & Accessories

12

Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

PLASTIC TEST CAPS

- Seal pipe ends economically
- For use on schedule 40 ABS and PVC DWV pipe
- Bright yellow color adds visibility for after-test removal

238 701	1-1/2"	Knock-Out™ Test Cap	100/1500	13 PSI	30FT
238 702	2"	Knock-Out™ Test Cap	100/1200	13 PSI	30FT
238 703	3"	Knock-Out™ Test Cap	50/500	13 PSI	30FT
238 704	4"	Knock-Out™ Test Cap	100/1500	13 PSI	30FT



228 108	1-1/2"	Push-Cap™ Test Cap	50/250	4.3 PSI	10FT
228 208	2"	Push-Cap™ Test Cap	25/125	4.3 PSI	10FT
228 308	3"	Push-Cap™ Test Cap	10/100	4.3 PSI	10FT
228 408	4"	Push-Cap™ Test Cap	10/50	4.3 PSI	10FT

238 108	1-1/2"	End-Cap™ Test Cap	100/1000	17 PSI	40FT
238 208	2"	End-Cap™ Test Cap	100/800	17 PSI	40FT
238 308	3"	End-Cap™ Test Cap	50/400	17 PSI	40FT
238 408	4"	End-Cap™ Test Cap	25/200	17 PSI	40FT

238 128	1-1/2"-2"	MS End-Cap™ Test Cap	50/500	17 PSI	40FT
238 348	3"- 4"	MS End-Cap™ Test Cap	25/200	17 PSI	40FT

PVC TEST-KAP® PLUGS

- Stainless steel hose clamp won't corrode
- For use on plastic, steel, copper, and cast-iron pipe
- Reinforced cross-molded top increases strength
- Tighten clamp with torque wrench or screwdriver to 60 inch pounds

270 725	1-1/2"	Test-Kap® Plug	1	13 PSI	30FT
270 733	2"	Test-Kap® Plug	1	13 PSI	30FT
270 741	3"	Test-Kap® Plug	1	13 PSI	30FT
270 768	4"	Test-Kap® Plug	1	13 PSI	30FT
270 776	5"	Test-Kap® Plug	1	13 PSI	30FT
270 784	6"	Test-Kap® Plug	1	13 PSI	30FT



TUB WASTE & OVERFLOW PLUGS

- Used to isolate bath wastes for air/water testing
- Natural rubber gasket creates air-tight seal
- 3/8" Drain thread
- Yellow ABS plastic ensures easy job site recognition
- For use on center hole drains overflow
- 1/4" Overflow thread

012 678		Tub Plug Set (overflow & drain)	1		
---------	--	---------------------------------	---	--	--

MANOMETER

- Used for final test of DWV pipe and to test gas lines
- Reads in 1/10" increments
- Measures water columns from 0" to 16"

010 205		Manometer	1		
---------	--	-----------	---	--	--



CLOG-BUSTER® DRAIN FLUSHER

- Unclogs drain pipes in seconds
- Simply remove aerator from faucet spigot and attach faucet adapter to garden hose
- Attaches to standard garden hose fitting
- Natural rubber body provides excellent seal

303 127	1"-2"	Drain Flusher	1		
303 135	1-1/2"-3"	Drain Flusher	1		
303 143	4"- 6"	Drain Flusher	1		
006193		Faucet Adapter	1		

